



CTM-MARINE

CT

High-efficient self-contained marine air conditioners.



10k / 16k BTU



High Velocity
Blower



<270° Rotatable
Blower



Quiet



Composite
Drain Pan



Compact



Cool/Heat



Titanium
Condenser Coil



Stainless Steel
Frame Base



Universal
Board



Re-usable
Air Filter



Fire Retardant
Electrical Box



Wi-Fi
Thermostats

www.ctm-marine.com

Air conditioners for the modern sailor.

Model No.	CT-10		CT-16	
Capacity (BTU)	10,000		16,000	
Voltage (V)	105-120	208-230	105-120	208-230
Cycle (Hz)	50 / 60		50 / 60	
Input: Cool (A)	6.7	3.3	10.5	5.1
Input: Heat (A)	8.8	3.9	13.5	6.6
Fuse Max/Min (A)	25/16	15/10	40/25	20/12
Locked Rotator Amps (A)	42	22	60	34
Refrigerant Type	R410A			
Seawater Inlet Connection (in/mm)	5 / 8 / 16			
Height (H) (in/mm)	13 / 330		14 / 356	
Width (W) (in/mm)	20 / 508		20 / 508	
Max. Depth (D) (in/mm)	12 / 305		13.5 / 343	
Min. Return Air Grille (sq in / sq cm)	100 / 646		160 / 1033	
Min. Supply Air Grille (sq in / sq cm)	60 / 388		80 / 517	
Min. Duct Diameter (in / mm)	5 / 127		6 / 152	
Min. Duct Area (sq in / sq cm)	28.3 / 183		38.5 / 248	
Net Weight (lbs/kg)	50 / 23		60 / 27	
Gross Weight (lbs/Kg)	53 / 24		64 / 31	

